SC2-100
Systems Integration Amplifier



2-Channel Bridgeable Power Amplifier

The Nice SC2-100 Offers the classic power and stability that you've come to know and trust. The Nice SC2-100 brings extremely high current power to a custom installed A/V System in a remarkably convenient way. Featuring audio circuitry constructed using the finest materials available including 1% metal film resistors, high quality capacitors and oversized heat sinks that ensure power cooling without the need for a noisy fan.

2-Channel Amplifier

The Nice SC2-100 Amplifier provides 100W per channel (400W when bridged for higher output applications) and independent level control, making installation easier and more straight forward than ever before.

SPEAKERCRAFT
a Nice brand

SC2-100 Systems Integration Amplifier



Features

- **Real World Power**
  The Nice SC2-100 delivers 100 watts per channel at 8 ohms and 200 watts per channel at 4 Ohms
- **Turn-On Modes**
  The Nice SC2-100 Amplifier features three turn-on modes: Music Sense, External Voltage Trigger and Manual Turn-On via the front panel switch
- **Bridged Mode**
  The Nice SC2-100 amplifier can be operated in a bridged mono configuration, delivering 400 watts
- **Independent Level Controls**
  Each amplifier channel features independent level control enabling precise volume matching to the rest of the system
- **Freedom from Fan Nose**
  The oversized heat sinks inside the System Integration Amplifiers allows the amplifier circuitry to stay cool even when operating into low impedance loads without noise
- **Current for Reactive Loads**
  The Nice SC2-100 amplifiers assures that even unusual and reactive loads are handled with ease. Cutting edge digital power supplies provide more than ample current to your system
- **Freedom for Cross-Talk**
  This increases the isolation between channels and eliminates cross talk, guaranteeing you absolute silence as the backdrop to your music
- **Control Output**
  A 12V DC output is provided whenever the amplifier is on, allowing you to operate voltage triggered devices

Specifications

Power Consumption	100 watts RMS per channel into 8 Ohms (all channels driven) 220 watts RMS per channel into 4 Ohms (all channels driven) Channels are bridgeable to 400 watts RMS into 8 Ohms
Total Harmonic Distortion	0.2% THD from 20Hz to 20kHz
Control out	12V
Line cord	Removable
Warranty	2-year warranty
Certification	Tested and Certified to US, Canada, EU and Australian safety and EMC Standards

Dimensions	(in) 17 ¼ W x 2 ¼ H (cm) 43.81W x 5.6 H (Including feet)
Number of Channels	2
Watts RSM Per Channel	100
Shipping Info	Length: 23" Width: 16.7" Height: 5.7" Weight: 13.45 lbs Unit of Measure: Each UPC: 664254999666
Master Park Qty	2

Nice

Niceforyou.com

©2023 Nice North America LLC. All rights reserved.
All other products or name brands are trademarks of their respective holders.